

## WATER-COOLED INDOOR/OUTDOOR



The Water-Cooled Indoor/Outdoor Air Conditioners remove heat from the system by means of the water cooling the refrigerant. No external air movers or condenser coils required which could get clogged. They have an attractive design with minimal use of visible fasteners including easy-mount flanges for simple installation.

### FEATURES & BENEFITS

Heat is removed from the system by means of the water cooling the refrigerant; no external air movers or condenser coils to get clogged

Attractive industrial design with minimal use of visible fasteners

R134a refrigerant

Models for 115 and 230 VAC power input

Operating temperature range from 50 F/10 C to 125 F/52 C

Maximum water usage of 2 GPM at 90 F water intake temperature

Reliable mechanical thermostat located behind the front panel of the unit

Low-carbon mild-steel sheet-metal cover for rugged factory and outdoor environments

Easy-mount flanges for simple installation

Every unit functionally tested before shipping

Standard Indoor Air Conditioner models also include: Electro-Mechanical Thermostat, Surge Suppressor, Robust reciprocating compressor

Mounting hardware, gaskets and user manual furnished with the unit

## SPECIFICATIONS

**Material** Mild Steel

**Finish** Powder Coated

**Color** Light Gray

**Color Code** RAL 7035

**Thickness** 1.52 mm

Table 1/2

Catalog Number	Height	Width	Depth	Nominal Capacity Btu/h	Nominal Capacity Watts	Nominal Voltage
CR430816GW010	1100 mm	400 mm	260 mm	8500 Btu/h	2490 W	115 V
CR430826GW010	1100 mm	400 mm	260 mm	8500 Btu/h	2490 W	230 V

Table 2/2

Catalog Number	Voltage AC	Max Current	Operating Temperature	Protection Rating
CR430816GW010	100 V	13 A	10 – 55 °C	NEMA Type 12
CR430826GW010	200 V	6.5 A	10 – 55 °C	

**Material** Mild Steel

**Finish** Powder Coated

**Color** Light Gray

**Color Code** RAL 7035

**Thickness** 1.52 mm

Table 1/2

Catalog Number	Height	Width	Depth	Nominal Capacity Btu/h	Nominal Capacity Watts	Nominal Voltage
CR430816GW010	1100 mm	400 mm	260 mm	8500 Btu/h	2490 W	115 V
CR430826GW010	1100 mm	400 mm	260 mm	8500 Btu/h	2490 W	230 V

Table 2/2

Catalog Number	Voltage AC	Max Current	Operating Temperature	Protection Rating
CR430816GW010	100 V	13 A	10 – 55 °C	NEMA Type 12
CR430826GW010	200 V	6.5 A	10 – 55 °C	

**Material** Mild Steel

**Finish** Powder Coated

**Color** Light Gray

**Color Code** RAL 7035

**Thickness** 1.52 mm

Table 1/2

Catalog Number	Height	Width	Depth	Nominal Capacity Btu/h	Nominal Capacity Watts	Nominal Voltage
CR430816GW010	1100 mm	400 mm	260 mm	8500 Btu/h	2490 W	115 V
CR430826GW010	1100 mm	400 mm	260 mm	8500 Btu/h	2490 W	230 V

Table 2/2

Catalog Number	Voltage AC	Max Current	Operating Temperature	Protection Rating
CR430816GW010	100 V	13 A	10 – 55 °C	NEMA Type 12
CR430826GW010	200 V	6.5 A	10 – 55 °C	

2100 Hoffman Way  
Anoka, MN 55303-1745 | USA  
763.421.2240



Our powerful portfolio of brands:  
**nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.  
nVent reserves the right to change specifications without notice.